

CSN-80V/80L

3" POS Printer Series



- Max 250mm/s high speed printing, easy to maintain, improve work efficiency
- Low noise, high speed image & characters printing
- Easy paper loading, with auto cutter, partial cut
- Serial, USB, Ethernet interfaces optional. (Support two in one, or three in one)
- Support paper out alarm and print prompt
- Compatible with EPSON ESC/POS command sets

MODEL	CSN-80V CSN-80L
Print method	Thermal line printing
Paper width	79.5±0.5mm
Printing Width	72mm
Print Density	203dpi(8dots/mm)
Print speed	250mm/s(max)
Reliability	TPH Cutter
	100km(12.5% print ratio) 1,000,000 cuts or more
Character size	(ANK Character):12×24 dots,1.5(width)×3.00(height)mm (Jan/traditional form):24×24 dots,3.00(height)×3.00(high)mm
Character FLash	4M byte
MCU	Flash:0KB SRAM:200KB
Characters Set	ANK:Font A:12x24dots Font B:9x17dots Jan/traditional form:24x24dots
Dot print command	print full character and tab character
Barcode type	1D:UPC-A/UC-E/JAN13(EAN13)/CODABAR/ITF/CODE39/ CODE93/CODE128 2D:Double QR Code
Auto cutter	Partly cut and Full cut
Cashbox control	24V/1A(support 12V and 24V Cashbox)
Interface	CSN-80V:RS232C+USB+LAN CSN-80L:RS232+USB Width:79.5±0.5mm
Thermal paper roll	Maximum diameter:Φ80mm Paper thick 55-90 μm
Power supply	DC24V/2.0A
Printing command	Compatible with ESC/POS command set
Dimension (WxLxH)	148x198x145
Work environment requirements	Temperature 0° C~40° C;Relative humidity:10%~80%
Store environmental requirements	Temperature-20° C~60° C;Relative humidity:10%~90%
Drivers	Win2000/WinXP/Windows7/Windows10/Linux

