



■ Product Features

- High-value integrated appearance design
- 250 mm/s low noise, high-speed printing
- Support full/partial cut
- Support black mark detection
- Ultra-large capacity paper bin

■ Application



Catering



Logistics



Stock Market



Retail



Cinema

Product model		CSN-806	
Printing	Print mode	Direct Thermal	
	Print width	72mm	
	Print resolution	203dpi(8dots/mm)	
	Print speed max.	250mm/s	
Paper	Type	Thermal paper , black mark paper	
	Width	80mm	
	Roll paper diameter (O.D)	83mm	
	Thickness	0.055-0.09mm	
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24	
	Code page	48	
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93	
	2D barcode	QR Code,PDF417	
Interface	Standard	USB Type-B+LAN USB Type-B+RS232	
	Optional	BT / WIFI	
Sensor		Paper end, Black mark detection,Cutter home position,Platen position detection	
Reliability	Cutting method	Full/Partial cut	
	Cutter life	1,000,000 cuts	
	TPH life	100km	
Power Adapter	AC	AC100V-240V 50/60Hz	
	DC	DC24V/2A	
Cashbox control		DC24V 1A	
Dimensions	(WxLxHmm)	165x126x121mm	
Weight	kg	0.715kg	
Emulation	Compatiable	ESC/POS	
Software	Driver	Windows Driver,Linux Driver,OPOS Driver	
	SDK	Windows SDK,Android SDK; Linux SDK	
Environment	Temperature	Operating:0°C~50°C	Storage:-20°C ~ 60°C
	Humidity(No condensation)	Operating:20%RH~85%RH	Storage:10%~90%RH