



Product Features

- Low noise, high speed printing;
- Automatic paper feeding;
- Support full/partial cut;
- Centered printing;
- Paper detection function;
- Automatically eliminate stuck cutter function;
- Compatible with various paper width adjustments.

Application



ATM machine



Gas station



Vending



Charging pile



Number taking machine

product model		KP-302
Printing	Print mode	Direct Thermal
	Print width	72mm
	Print resolution	203dpi
	Print speed max.	250mm/s
Paper	Type	Thermal receipt, Black mark paper
	Width(Max)	82.5mm
	Roll paper diameter (O.D)	120mm
	Roll core inner diameter (Min.)	13/25mm
	Thickness	0.055-0.12mm
Character set	Font	Font A:12x24;Font B:9x17 GBK:24x24
	Code page	48
Barcode	1D barcode	UPC-A, UPC-E, JAN/EAN8, JAN/EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93
	2D barcode	QR Code,PDF417
Interface	Standard	USB+RS232
	Optional	USB+RS232+LAN
Sensor	Standard	Paper end, Paper near end ,Paper taken, Black mark detection
	Optional	Paper presence, Anti paper jam, Anti-drag ticket
Reliability	Cutting method	Full/Partial cut
	Cutter life	1,000,000cuts
	TPH life	100km
Input Power	AC	AC100V-240V 50/60Hz
	DC	DC24V,2A
Dimensions Weight Emulation	(WxLxHmm)	141.1x115.2x77mm
	kg	1.32kg
	Commands	ESC/POS
Software	Driver	Windows Driver,Linux Driver,OPOS Driver
	SDK	Windows SDK,Android SDK,Linux SDK
Environment	Temperature	Operating:-10°C~50°C Storage:-20°C ~ 70°C
	Humidity(No condensation)	Operating:20%RH~85%RH Storage:10%~90%RH